

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. **(Currently amended)** A device for inspecting an object (2), having a bright field illumination beam path (4) of a bright field light source (5) formed with respect to an imaging optical arrangement (3), having a dark field illumination beam path (6) of a dark field light source (7) formed with respect to the imaging optical arrangement (3), the object (2) being imaged onto at least one detector (8) by means of the imaging optical arrangement (3) and the object (2) being illuminated simultaneously by the two light sources (5, 7), characterized in that the light serving for dark field illumination is pulsed, and in that the pulse intensity of the light serving for dark field illumination is at least one order of magnitude greater than the intensity ~~[[–]] relative to a pulse interval [[–]] of the~~ continuous light serving for bright field illumination;

wherein the read-out and/or evaluation readiness of the detector (8) and/or of a detection system (46) is synchronized with the pulse sequence of the light serving for dark field illumination, ~~preferably on the basis of a pulse sequence signal of the dark field light source (7) or of a control signal of an optical component (13).~~

2. **(Currently amended)** The device as claimed in claim 1, characterized in that the pulse intensity of the light serving for dark field illumination is 10 to 10 000 times greater than the intensity ~~[[–]] relative to a pulse interval [[–]] of the~~ continuous light serving for bright field illumination.

3. **(Currently amended)** The device as claimed in claim 1, characterized in that the dark field light source (7) emits pulsed light.

4. **(Currently amended)** The device as claimed in claim 1, characterized in that the dark field light source ~~(7)~~ emits continuous light that can be subdivided into individual pulses by means of at least one optical component ~~(13)~~.

5. **(Currently amended)** The device as claimed in claim ~~[[1]]~~ 4, characterized in that the optical component ~~(13)~~ has a shutter, a rotating shutter wheel, an electro-optical or an acoustic-optical modulator.

6. **(Cancelled)**

7. **(Currently amended)** The device as claimed in claim 1, characterized in that a delay circuit ~~(18)~~ is provided for synchronization purposes.

8. **(Currently amended)** The device as claimed in claim 1, characterized in that the optical axis ~~(25)~~ of the bright field illumination beam path ~~(4)~~ is essentially perpendicular to the surface ~~(26)~~ of the object ~~(2)~~ to be inspected or is essentially perpendicular to the object plane of the imaging optical arrangement ~~(3)~~.

9. **(Currently amended)** The device as claimed in claim 1, characterized in that the optical axis ~~(27)~~ of a detection beam path ~~(9)~~ running between the object ~~(2)~~ and detector ~~(8)~~ is essentially perpendicular to the surface ~~(26)~~ of the object ~~(2)~~ to be inspected or is essentially perpendicular to the object plane of the imaging optical arrangement ~~(3)~~.

10. **(Currently amended)** The device as claimed in claim 1, characterized in that the optical axis (28) of the dark field illumination beam path (6), at least in regions, is coaxial with the optical axis (25) of the bright field illumination beam path (4) and/or coaxial with the optical axis (27) of a detection beam path (9).

11. **(Currently amended)** The device as claimed in claim 1, characterized in that the optical axis (28) of the dark field illumination beam path (6) has an angle (29) of between 5 and 90 degrees with respect to the optical axis (25) of the bright field illumination beam path (4) and/or with respect to the optical axis (27) of a detection beam path (9).

12. **(Currently amended)** The device as claimed in claim 1, characterized in that the bright field light source (5) is designed as a white light source, ~~preferably a DC lamp.~~

13. **(Currently amended)** The device as claimed in claim 1, characterized in that the dark field light source (7) is designed as a xenon flash lamp, a laser or an LED (Light Emitting Diode) or an LED arrangement.

14. **(Currently amended)** The device as claimed in claim 1, characterized in that the detector (8) is designed as a CCD camera.

15. **(Currently amended)** The device as claimed in claim 1, ~~characterized by~~ further comprising a coupling to a control computer, ~~which preferably has a storage unit on which the detected object data can be stored.~~

16. **(Currently amended)** A method for inspecting an object (2), the object (2) being illuminated simultaneously with a bright field light source (5) for bright field illumination, on the one hand, and with a dark field light source (7) for dark field illumination, on the other hand, and the object (2) being imaged onto at least one detector (8) by means of an imaging optical arrangement (3), ~~preferably for operating a device as claimed in claim 1,~~ characterized in that the light serving for dark field illumination is pulsed, the pulse intensity of the light serving for dark field illumination being at least one order of magnitude greater than the intensity ~~relative to a pulse interval~~ of the continuous light serving for bright field illumination.

17. **(Original)** The method as claimed in claim 16, characterized in that the object inspection is carried out automatically.

18. **(Currently amended)** The method as claimed in claim 16, characterized in that ~~the~~ a device (4) is coupled to a positioning system (30) that positions the object (2), and in that object regions selected by means of the positioning system (30) are automatically positioned in the inspection position.